

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **09037382 A**(43) Date of publication of application: **07.02.97**

(51) Int. Cl.


H04R 3/00**H01C 7/02****H04R 1/04**(21) Application number: **07213895**(22) Date of filing: **19.07.95**(71) Applicant: **HONDA MOTOR CO LTD**

(72) Inventor:
HOSOI TAKASHI
NISHIO TOMOYUKI
DOI MIZUHO
FUEKI NOBUHIRO
YAMAKAWA HIROSHI

(54) MICROPHONE**(57) Abstract:**

PROBLEM TO BE SOLVED: To make it possible to highly sensitively detect a sound even by a microminiaturized microphone by detecting a change in a resistance value obtained when a heat sensitive resistor formed on a diaphragm formed on a base board 1 by micromachining work is oscillated as an electric signal.

SOLUTION: A diaphragm 2 consisting of a thin film is formed on a base board 1 by micromachining work. A heat sensitive resistor consisting of a heat wire 3 having a large resistance temperature coefficient is formed on the surface of the diaphragm 2 and electrode parts 4 are formed on the end parts of the diaphragm 2. A constant current power supply 5 is connected to the heat wire 3 through the electrode part 4 to heat the wire 3 always at a fixed temperature. When the diaphragm 2 is oscillated by the input of a sound from the upper face, the wire 3 is cooled by air and its resistance value is changed. Thereby the terminal voltage of the wire 3 is changed and the change is detected by a voltage variation forming circuit 6, so that an output signal V_o corresponding to the input sound is obtained. Thus a microminiaturized microphone can be attained by micromachining work and a sound can be highly accurately detected.



COPYRIGHT: (C)1997,JPO